

Fiche Technique Sécheur réfrigérant



Photo non contractuelle

Item	DAD-1 HTF	DAD-2 HTF	DAD-3 HTF	DAD-6 HTF	DAD-8 HTF	DAD-10 HTF	DAD-13 HTF	DAD-15 HTF	DAD-20 HT(N)F	DAD-25 HT(N)F	DAD-30 HT(N)F	DAD-40 HT(N)F	DAD-50 HT(N)F	DAD-60 HT(N)F
Capacité (Nm ³ /min)	1.2	2.4	3.8	6.5	8.0	10.7	13.8	17.0	23.0	27.0	33.0	45.0	55.0	65.0
Tension(V/Hz)	220/50	220/50	220/50	220/50	220/50	220/50	380/50	380/50	380/50	380/50	380/50	380/50	380/50	380/50
Puissance de compresseur (KW)	0.75	0.75	0.90	1.50	1.80	2.20	2.60	3.70	4.40	5.40	8.50	8.50	8.80	10.0
Puissance de ventilateur(W)	75	110	130	250	250	2*195	2*195	2*195	2*240	2*240	2*240	3*240	3*520	3*520
Diamètre de tuyau d'entrée / sortie d'air	ZG1	ZG1	ZG1	ZG1-1/2	ZG1-1/2	ZG2	ZG2	DN80	DN80	DN80	DN80	DN100	DN125	DN125
Poids	50	57	78	120	140	155	175	350	430	600	650	720	950	1000
Dimensions	L(mm)	640	600	760	820	820	1150	1190	1400	1660	1820	1810	2190	2430
	W(mm)	400	460	480	550	550	540	600	800	850	800	950	950	1110
	H(mm)	580	670	750	880	880	1000	1030	1245	1370	1370	1588	1588	1620

Le paramètre technique du sécheur d'air refroidi par l'eau :

Item	DAD-15 HTW	DAD-20 HTW	DAD-25 HTW	DAD-30 HTW	DAD-40 HTW	DAD-50 HTW	DAD-60 HTW	DAD-80 HTW	DAD-100 HTW	DAD-120 HTW	DAD-150 HTW	DAD-180 HTW	DAD-200 HTW	DAD-300 HTW	
Capacité (Nm3/min)	17	23	27	33	45	55	65	85	100	120	150	180	200	300	
Tension(V/Hz)	380/50	380/50	380/50	380/50	380/50	380/50	380/50	380/50	380/50	380/50	380/50	380/50	380/50	380/50	
Puissance de compresseur (KW)	3.7	4.4	5.4	8.5	8.5	8.8	10.0	13.6	18.7	23.5	27.6	33.6	37.3	59.7	
Capacité d'eau de refroidissement(m3/h)	3.0	3.7	4.4	5.9	7.4	8.9	11.1	12.4	14.6	16.5	18.6	21.6	24.4	36.0	
Diamètre de tuyau d'entrée/sortie d'air	DN80	DN80	DN80	DN80	DN100	DM125	DM125	DM125	DN150	DN150	DN200	DN200	DN200	DN250	
Diamètre du tuyau d'eau du condenseur	R1	R1	R1.5	R1.5	R1.5	R1.5	R2	R2	R2	R2.5	R2.5	DN80	DN80	DN80	
Poids	350	405	550	600	660	950	995	1490	2250	2460	2750	3200	3250	3900	
Dimensions	L(mm)	1400	1470	1790	1710	1990	2090	2265	2320	2690	2980	3070	3300	3360	4000
	W(mm)	800	800	800	950	950	1000	1020	1240	1160	1260	1500	1650	1600	1980
	H(mm)	1145	1370	1370	1588	1588	1483	1636	1674	2050	2120	2466	2226	2720	2380

*) Les spécifications sont susceptibles de changer sans préavis